

# GORI 44+ QUICK DRY

## Translucent Wood Stain



**GORI 44+ Quick Dry Translucent Wood Stain** is an alkyd modified, water based, semi-translucent wood protection which enhances the natural structure of the wood. GORI 44+ Quick Dry Translucent Wood Stain gives the wood a decorative and weather resistant surface whilst protecting against the sun's UV-rays and preventing surface fungi and mould. Ideal for use on cladding, fences and exterior structures. Can be used on new and previously treated wood.



### KEY PROPERTIES

- ▶ For cladding, fences and exterior structures
- ▶ Protects against UV-rays, fungi and mould - prevents flaking, peeling and cracking
- ▶ Quick dry, semi-transparent wood protection, which enhances the natural grain of the wood

### PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Loose fibres and old paint must be removed and decayed wood must be replaced. To obtain maximum performance from this product, old paint and varnish should be completely removed. Treat fungal or algal growth with a Sterilisation Wash as directed. Treat bare timber surfaces with an GORI 11 Wood Preservative\* as directed. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparations of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information on our products and service please call 01924 354354.

### APPLICATION

Ensure good ventilation during application and drying. Apply by brush or roller. Stir well.

Do not apply when moisture of the wood is above 18% at the time of treatment or if the temperature is below +5°C and relative humidity is below 80%. Avoid application in damp conditions or externally when rain is imminent. Never apply wood protection in direct sunlight.

Apply one coat of GORI 11 Wood Preservative\* as directed before applying two coats of GORI 44+ Quick Dry Translucent Wood Stain.

Please note that the final colour result depends on the colour of the substrate. If more than one can of the same colour is to be used in the same area, intermix before use. Additional coats may be required in certain colours or when attempting a wide colour change.

### COVERAGE

GORI 44+ Quick Dry Translucent Wood Stain will cover approximately 9-12 m<sup>2</sup>/l.

### DRYING TIME

Touch dry: 1 hour. Recoatable with GORI 44+: 4 hours . Touch dry: app. 24 hours. (measured at 23°C and standard humidity of 60%).

### CLEANER

Clean Water

### COLOUR RANGE

Available in a tintable colour range.

### SIZE

Available in 0.75L & 5L

### AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

### STORAGE

PROTECT FROM FROST

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care – gross weight does not exceed 8 kilograms. As wood is an organic material, there is no guarantee that the same wood species will react the same way in different areas, when treated/coated/stained.

EU limit value for this product (Cat A/e): 130g/l (2010).

This product contains max 30g/l VOC.

### SAFE USE INFORMATION

Keep out of reach of children.

Avoid contact with skin and eyes.

Do not ingest.

Do not breathe spray. Wear respiratory protection.

If medical advice is needed have container or label to hand.

Please refer to Product label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.

SDS available by calling 01924 354 354.

\*GORI 11 Wood Preservative is not available in the Republic of Ireland.



DATE OF ISSUE: 15.01.2021  
VERSION: 1  
PRODUCT EMG: 10130RUK13X44

**GORI**  
Professional